



UNLESS SPECIFIED: ALL DIMENSIONS IN INCHES GENERAL TOLERANCES: 3 PLACE ±.005 2 PLACE ±.01 ANGULAR ±2°	SCALE: 4 : 1 DWG SIZE: B DRAWN BY & DATE: DW 3-30-11 CHECKED BY & DATE: APPROVED BY & DATE:	THIRD ANGLE PROJECTION	REVISE ON CAD ONLY
QUALITY SYMBOLS: MAJOR: = 0 CRITICAL: C / = 0 SPC: S / = 0	UNLESS SPECIFIED: ALL DIMENSIONS IN INCHES GENERAL TOLERANCES: 3 PLACE ±.005 2 PLACE ±.01 ANGULAR ±2°	TITLE: CONNECTOR ASSEMBLY, MR21P07-26M5-36.0	
Uti-Mate CAGE CODE 58967	CAD FILENAME SD-834130397.DGN	MATERIAL: Uti-Mate Connector Inc.	DRAWING NO. SD-834130397
			SHEET NO. 1 OF 1
			REV -

2 MATERIALS:
SHELL: 6061-T6 OR 6061-T651 ALUMINUM PER SAE-AMS-00-A200/8, CAD PLATED PER SAE-AMS-00-P-416
INSULATOR: PPS PER MIL-M-24519 GST-40F, COLOR: BLACK
PIN CONTACTS: C17200 BERYLLIUM COPPER PER ASTM B194, GOLD PLATED PER ASTM B488
HARDWARE: STAINLESS STEEL IAW MIL-DTL-83513, PASSIVATED
1. MARKING: UMI, DATE CODE, UMI P/N.
NOTES: UNLESS OTHERWISE SPECIFIED.

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO ULTI-MATE INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.